



The World's Largest Open Access Agricultural & Applied Economics Digital Library

This document is discoverable and free to researchers across the globe due to the work of AgEcon Search.

Help ensure our sustainability.

Give to AgEcon Search

AgEcon Search
<http://ageconsearch.umn.edu>
aesearch@umn.edu

Papers downloaded from AgEcon Search may be used for non-commercial purposes and personal study only. No other use, including posting to another Internet site, is permitted without permission from the copyright owner (not AgEcon Search), or as allowed under the provisions of Fair Use, U.S. Copyright Act, Title 17 U.S.C.

No endorsement of AgEcon Search or its fundraising activities by the author(s) of the following work or their employer(s) is intended or implied.

THE STATA JOURNAL

Editor

H. Joseph Newton
Department of Statistics
Texas A & M University
College Station, Texas 77843
979-845-3142; FAX 979-845-3144
jnewton@stata-journal.com

Editor

Nicholas J. Cox
Geography Department
Durham University
South Road
Durham City DH1 3LE UK
n.j.cox@stata-journal.com

Associate Editors

Christopher Baum
Boston College
Rino Bellocchio
Karolinska Institutet
David Clayton
Cambridge Inst. for Medical Research
Mario A. Cleves
Univ. of Arkansas for Medical Sciences
William D. Dupont
Vanderbilt University
Charles Franklin
University of Wisconsin, Madison
Joanne M. Garrett
University of North Carolina
Allan Gregory
Queen's University
James Hardin
University of South Carolina
Ben Jann
ETH Zurich, Switzerland
Stephen Jenkins
University of Essex
Ulrich Kohler
WZB, Berlin
Jens Lauritsen
Odense University Hospital

Stanley Lemeshow
Ohio State University
J. Scott Long
Indiana University
Thomas Lumley
University of Washington, Seattle
Roger Newson
King's College, London
Marcello Pagano
Harvard School of Public Health
Sophia Rabe-Hesketh
University of California, Berkeley
J. Patrick Royston
MRC Clinical Trials Unit, London
Philip Ryan
University of Adelaide
Mark E. Schaffer
Heriot-Watt University, Edinburgh
Jeroen Weesie
Utrecht University
Nicholas J. G. Winter
Cornell University
Jeffrey Wooldridge
Michigan State University

Stata Press Production Manager

Lisa Gilmore

Copyright Statement: The Stata Journal and the contents of the supporting files (programs, datasets, and help files) are copyright © by StataCorp LP. The contents of the supporting files (programs, datasets, and help files) may be copied or reproduced by any means whatsoever, in whole or in part, as long as any copy or reproduction includes attribution to both (1) the author and (2) the Stata Journal.

The articles appearing in the Stata Journal may be copied or reproduced as printed copies, in whole or in part, as long as any copy or reproduction includes attribution to both (1) the author and (2) the Stata Journal.

Written permission must be obtained from StataCorp if you wish to make electronic copies of the insertions. This precludes placing electronic copies of the Stata Journal, in whole or in part, on publicly accessible web sites, fileservers, or other locations where the copy may be accessed by anyone other than the subscriber.

Users of any of the software, ideas, data, or other materials published in the Stata Journal or the supporting files understand that such use is made without warranty of any kind, by either the Stata Journal, the author, or StataCorp. In particular, there is no warranty of fitness of purpose or merchantability, nor for special, incidental, or consequential damages such as loss of profits. The purpose of the Stata Journal is to promote free communication among Stata users.

The *Stata Journal*, electronic version (ISSN 1536-8734) is a publication of Stata Press, and Stata is a registered trademark of StataCorp LP.


Stata tip 23: Regaining control over axis ranges

Nicholas J. G. Winter
Cornell University
nw53@cornell.edu

Beginning with version 8, Stata will often widen the range of a graph axis beyond the range of the data. Convincing Stata to narrow the range can be difficult unless you understand the cause of the problem.

Using the trusty `auto` dataset, consider the graph produced by this command:

```
. sysuse auto, clear  
(1978 Automobile Data)  
. twoway scatter mpg price
```



Although price ranges from \$3,291 to \$15,906 in the data, the lower end of the x -axis in this graph extends to zero, leaving blank space on the left-hand side. If we do not like this space, the solution would seem to lie with the `range()` suboption of the `xscale()` option. Thus we might expect Stata to range the x -axis using the minimum and maximum of the data, given the following command:

```
. twoway scatter mpg price, xscale(range(3291 15906))
```

However, this produces the same graph: the axis still includes zero. It seems that Stata is ignoring `range()`, although it does not do that when the range is *increased*, rather than decreased. Consider, for example, this command, which expands the x -axis to run from 0 through 30,000:

```
. twoway scatter mpg price, xscale(range(0 30000))
```


The issue is that the range displayed for an axis depends on the interaction between two sets of options (or their defaults): those that control the axis range explicitly, and those that *label* the axis. The range can be expanded either by explicitly specifying a longer axis (e.g., with `xscale(range(a b))`) or by labeling values outside the range of the data.

To determine the range of an axis, Stata begins with the minimum and maximum of the data. Then it will widen (but never narrow) the axis range as instructed by `range()`. Finally, it will widen the axis if necessary to accommodate any axis labels.

By default, `twoway` labels the axes with “about” five ticks, the equivalent of specifying `xlabel(#5)`. In this case, Stata chooses four labels, one of which is zero, and then expands the *x*-axis accordingly. In other words, if we specify `xscale()`—but do not specify `xlabel()`—we are in effect saying to Stata “and please use the default `xlabel()` for this graph”. This default may widen the axis range.

Therefore, to get a narrower *x*-axis, we must specify a narrower set of axis labels. For example, to label just the minimum and maximum, we could specify

```
. scatter mpg price, xlabel(minmax)
```



Of course, we could specify any other set of points to label, for example,

```
. scatter mpg price, xlabel(5000[1000]15000)
```

This issue only appeared with Stata version 8. Prior versions defaulted to labeling the minimum and the maximum of the data only. This would be equivalent to including the options `xlabel(minmax)` and `ylabel(minmax)` in Stata 8 or later.