



AgEcon SEARCH
RESEARCH IN AGRICULTURAL & APPLIED ECONOMICS

The World's Largest Open Access Agricultural & Applied Economics Digital Library

This document is discoverable and free to researchers across the globe due to the work of AgEcon Search.

Help ensure our sustainability.

Give to AgEcon Search

AgEcon Search
<http://ageconsearch.umn.edu>
aesearch@umn.edu

*Papers downloaded from **AgEcon Search** may be used for non-commercial purposes and personal study only. No other use, including posting to another Internet site, is permitted without permission from the copyright owner (not AgEcon Search), or as allowed under the provisions of Fair Use, U.S. Copyright Act, Title 17 U.S.C.*

**Irrigation water use efficiency in central Tunisian's wheat production systems:
A stochastic data envelopment approach**

Ali CHEBIL, Kais ABBAS and Aymen FRIJA

*Invited paper presented at the 4th International Conference of the African Association
of Agricultural Economists, September 22-25, 2013, Hammamet, Tunisia*

*Copyright 2013 by [authors]. All rights reserved. Readers may make verbatim copies of
this document for non-commercial purposes by any means, provided that this copyright
notice appears on all such copies.*

**Irrigation water use efficiency in central Tunisian's wheat production systems:
A stochastic data envelopment approach**

Ali CHEBIL⁽¹⁾, Kais ABBAS⁽¹⁾ and Aymen FRIJA⁽²⁾

⁽¹⁾ Institut National de Recherches en Génie Rural, Eaux et Forêts (INRGREF)
B.P. 10, 2080, Ariana, Tunisie
E-mail chebila@yahoo.es

⁽²⁾ Ecole Supérieure d'Agriculture (ESA) Mograne, Zaghouan, 1121
Tunisia

Irrigation water use efficiency in central Tunisian's wheat production systems: A stochastic data envelopment approach

Abstract

This study employs stochastic DEA approach for measuring irrigation water efficiency of wheat farms in irrigated areas of Chbika (Central Tunisia). Data was collected from 170 wheat farms during 2010-2011 cropping season. The empirical results show that the average water use efficiency calculated by this approach was only around 41% under CRS while it was 44% under VRS. This suggests that there is substantial scope for improving irrigation water use efficiency in the study region using the existing technology on wheat farms. A Tobit regression was used to identify the determinants of the irrigation water use efficiency in the studied sample. Results of the Tobit analysis show the positive effect on water use efficiency of variety choices, irrigation sources, membership in water users associations, irrigation management and experience. These results are valuable for policy makers since they can be easily integrated in the general guidelines of water valorisation policies.

Keywords: Irrigation water efficiency, Stochastic Data Envelopment Analysis, Tobit model, Wheat farms, Tunisia

1. Introduction

Tunisian agricultural production is nowadays faced to an increased water scarcity due to the growing demand of water and to the climate change. Tunisia is characterized by low rainfall and limited renewable water resources. It is influenced by the arid and semi-arid climate that covers more than $\frac{3}{4}$ of its area. Agricultural sector, which accounts for less than 12% of the GDP, is highly dependent on water resources since it consumes more than 80% of total water use in the country. Irrigated area in Tunisia occupies 8% of total agricultural surface but it contributes with 35% of agricultural production, 22% of exports, and 26% of agricultural 27 % of agricultural employment (Al Atiri R., 2007). This performance is mainly due to the significant expansion of irrigated areas (Al-Atiri, 2009), which passed from 250,000 ha in 1990 to 450,470 ha in 2010 (MA, 2011). However, the limited water resources in the near future and the limited supply of cultivable land preclude the potential for further expansion of irrigated areas in Tunisia. In fact, fresh water mobilization has reached its limits and any further investments for water mobilization will be highly costly.

In spite of its evident scarcity, the present use of water in agriculture indicates that irrigation as practices in Tunisia is still inefficient and much of the used water for irrigation can be saved. In fact, several farm level studies showed that irrigation water use efficiency is very low and ranges between 40% and 60% (Dhehibi et al. 2007; Albouchi et al., 2007; Frija et al. 2009; Naceur et al, 2010; Chemak, 2010; Chebil et al., 2012).

The importance of water use efficiency takes on a new dimension when scarcity is considered. Water scarcity problem in Tunisia will become more severe as the government seeks to

overcome food supply problems through the expansion of agricultural production to new land. Additionally, industrial, domestic, touristic and environmental uses compete with agriculture for a relatively fixed volume of available water supply. Improvements in water use efficiency are an essential element in attempting to mitigate water scarcity and ensure optimal irrigation water use in the agricultural sector (Frija et al., 2009). Given the large amount of water consumed by the irrigation sector in Tunisia, improving on-farm water use efficiency can contribute directly to increased supply of water for other agricultural and non-agricultural uses. Therefore, studies on water use efficiency differentials among farmers samples are needed in order to improve water conservation by identification of the main factors at the origin of the inefficient use.

Stochastic frontier production (SFP) function and deterministic Data Envelopment Analysis (DEA) are the most used approaches in literature to measure the irrigation water use efficiency (IWUE). From methodological point of view, each of these methods has some advantages and disadvantages. The main advantage of SFA approach is that the frontier is stochastic and allows the effects of noise to be separated from the effects of inefficiency. However, it needs a prior specification of functional form of the production function and of the distribution of the one sided error term. The deterministic DEA approach avoids these limitations but attributing all the deviations from the frontier to inefficiencies and becomes then likely to be sensitive to outliers (Coelli, 2005).

In many important situations inputs or outputs of the decision making unit (DMU) are often considered to be random, so technical efficiency conclusions based upon a deterministic DEA analysis can be misleading because of the high sensitivity of the efficiency scores to the levels of inputs or outputs. Stochastic DEA (SDEA) methods have therefore been suggested to deal with these uncertainty problems.

In this study, our objective is to calculate the water use efficiency of the durum wheat systems of central Tunisia, using SDEA. In fact, wheat is a major cereal in Tunisia in terms of its output and cultivated land area. It occupies about 50% of all cereals area (800,000 Ha on average) and represents almost 55% of the total cereals production (average wheat production is around 1.8 million tons) (MA, 2010). Irrigated wheat area is around 80,000ha (MA, 2011). Considering the social and economic importance of the wheat sub-sector in Tunisia, the potential increase of IWUE should be a major concern for policy makers.

The rest of this paper is presented as follows. In section 2 the methodology used will be detailed. Empirical results are presented in section 3. Finally, in section 4 concluding remarks are drawn.

2. METHODOLOGICAL FRAMEWORK

Efficiency can be defined as producing a maximum amount of output, given a fixed amount of inputs (Output oriented); or producing a given level of output using a minimum level of inputs (input oriented); or a mixture of both. Efficient farms either use less input than others to

produce a given quantity of output, or for a given set of inputs they generate a greater output. Hence, the production function describes a frontier. If the production frontier is known, the technical inefficiency of any particular firm can be assessed easily by simply comparing the position of the firm relative to the frontier.

The two main approaches used for the efficiency measurement are DAE deterministic and stochastic frontier Analysis (SFA). This later model appends an error term, assuming two components: one is symmetric, capturing statistical noise and random shocks, and the other is one-sided, representing technical inefficiency effects. By far the most serious impediment to a wider acceptance of DEA as a valid analytical method in economic is that it is seen not distinguishing inefficiency from random shock. One has to specify the appropriate DEA model in order to obtain a proper measurement of the efficiency of a farm (Land et al, 1993; Olesen and Petersen, 1995; Seiford, 1996). Following Land et al. (1993), we assume that input values are deterministic, so that only the outputs are to be represented as random variables.

Recently, some advances in sub-vector efficiency calculation from the DEA models and from the stochastic frontier production are achieved. The sub-vector efficiency measure looks at the possible reduction in a selected subset of inputs holding all other inputs and outputs constant (Färe et al., 1994; Oude Lansink et al., 2002; Oude Lansink and Silva, 2004; Speelman et al., 2008). The main features of the conventional and SDEA to analyse the subvector efficiencies of inputs are described below. In this study we also opt for this assumption because in agricultural production increasing the inputs does not usually result in a proportional increase in output (Speelman et al., 2008)

2.1. Stochastic DEA approach of water use efficiency calculation

2.2.1. Deterministic DEA model

Mathematically, the input-oriented DEA model can be written as follows (See Färe et al., 1994, Oude Lansink and Silva, 2004; Lilienfeld and Asmild (2007), Speelman and al., 2008, and Frija, 2009 for more details about standard DEA subvector efficiency models):

$$\begin{aligned}
 & \text{Min}_{\theta, \lambda} \theta^s \\
 & \text{s.t.} \quad \sum_{k=1}^K \lambda_k y_{m,k} \geq y_{m,o} \\
 & \quad \sum_{k=1}^K \lambda_k x_{s,k} \leq \theta^s . x_{s,o} \\
 & \quad \sum_{k=1}^K \lambda_k x_{n-s,k} \leq x_{n,o} \\
 & \quad \sum_{k=1}^K \lambda_k = 1
 \end{aligned} \tag{1}$$

$$\lambda_k \geq 0$$

The θ^s in the resulting subvector model is the IWUE score of each farm. λ_k is a vector of k elements representing the contribution of each farm in determining the technical efficiency of the farm under consideration (farm₀); x_{n0} and y_{m0} are, respectively, the input and the output vectors of farm₀. For more information about the use of a subvector-DEA model for the calculation of IWUE see e.g. Lilienfeld and Asmild (2007), Speelman et al. (2008) and Frija et al. (2009). The IWUE score can be calculated for a given farm by looking at the possible reduction in the water use holding all other inputs and outputs constant.

2.2.2. Stochastic model

Following Land et al (1993), we assume that input values are deterministic, so that only the outputs are to be represented as random variables with a normal distribution. This allows the constraints to hold with the probability level $(1-\alpha)$. Hence, the SDEA for model (1) can be formulated as:

$$\begin{aligned} & \text{Min}_{\theta, \lambda} \theta^s \\ & \text{s.t. } \Pr \left\{ \sum_{k=1}^K \lambda_k y_{m,k} \geq y_{m,o} \right\} \geq (1-\alpha) \\ & \sum_{k=1}^K \lambda_k x_{s,k} \leq \theta^s x_{s,o} \\ & \sum_{k=1}^K \lambda_k x_{n-s,k} \leq x_{n,o} \\ & \sum_{k=1}^K \lambda_k = 1 \\ & \lambda_k \geq 0 \end{aligned} \quad (2)$$

Where Pr means “probability” and α is a predetermined scalar between 0 and 1. We set α at the conventional level of 0.05.

At this point, assume that each output y_k is normally distributed with mean μ_k and variance σ_k^2 . Further assume that $\text{Cov}(y_j, y_k) = 0$. Now, define the random variable

$$u = \sum_{k=1}^K \lambda_k y_k - y_0 \quad (3)$$

Then,

$$E(u) = \sum_{k=1}^K \lambda_k u_k - u_0 = u_u \quad (4)$$

And

$$\text{Var}(u) = \sum_{k=1, k \neq o}^K \lambda_k^2 \sigma_k^2 + (\lambda_k - 1)^2 \sigma_o^2 = \sigma_u^2 \quad (5)$$

The random variable representing the output shortfall is normally distributed because the y_k 's have the normal distribution:

$$z = \frac{u - u_u}{\sigma_u}$$

Hence

$$\Pr\left\{\sum_{k=1}^K \lambda_k y_k \geq y_o\right\} = \Pr\{u > 0\} = \Pr\left\{z \geq \frac{-u}{\sigma_u}\right\} \quad (6)$$

But, because of symmetry property of the normal distribution

$$\Pr\left\{z \geq \frac{-u}{\sigma_u}\right\} = \Pr\left\{z \leq \frac{u}{\sigma_u}\right\} = \Phi\left(\frac{u}{\sigma_u}\right) \quad (7)$$

Where Φ represent the cumulative distribution function of the standard normal variable. Consequently, the probability statement for the typical output constraint can be replaced by the equivalent restriction $\Phi\left(\frac{u}{\sigma_u}\right) \geq (1 - \alpha)$ (8)

2.2. Tobit model

The present study use the Tobit model to analyse the role of farm attributes in explaining IWUE This approach has been used widely in efficiency literature (Speelman and al., 2008, Naceur et al, 2010; Chebil et al., 2012). In fact, the values of the dependent variable (IWUE scores) lie in the interval (0,1). The censored Tobit model can be then used to get consistent estimation. Tobit model used in our study is specified as follows:

$$IWUE_i = \begin{cases} IWUE_i^* & \text{if } 0 < IWUE^* < 1 \\ 0 & \text{if } IWUE^* \leq 0 \\ 1 & \text{if } IWUE^* \geq 1 \end{cases} \quad (9)$$

Where IWE_i the observed dependent variable (IWUE) for the i th farm; $IWUE_i^*$ is a unobserved latent (hidden) variable for the i th IWUE farm that is observed for values greater than 0 and censored for values less than or equal to 1.

$$IWUE^* = X_i \beta + \varepsilon_i \quad (10)$$

Where X_i is a vector of independent variables supposed to influence efficiency. The β 's are parameters associated with the independent variables to be estimated. The ε is the independently distributed error term assumed to be normally distributed with a mean of zero and a constant variance $N(0, \sigma^2)$. Since the dependent variable of IWUE varies between 0 and 1, Least Ordinary Square (LOS) would produce biased and inconsistent estimates (Maddala, 1983). Therefore, the maximum likelihood estimation is recommended for Tobit analysis.

3. Data and variables definitions

The data employed in this study consists of information about the production structure of 170 Tunisian wheat farms. In order to ensure homogeneity in land and weather conditions, the farms in the sample have been chosen from Chbika region situated in Kairouan province, which is located in the centre of Tunisia. Chbika is facing growing problems of water scarcity. It is located in the semi-arid bioclimatic lower floor and characterised by moderate winter. Groundwater represents the main water source. The data used in the study was collected in 2011 with the collaboration of the extension service in the region, through a questionnaire to cereal-growing farmers.

Wheat production value per ha is used as output of the subvector efficiency model described in the previous section. In addition, three inputs (labour, water and fertilisers) are also included in the estimation of the SDEA model. Table 1 presents a summary statistics of output and inputs data used for our case study. As it can be seen, the average annual production value of wheat in the study area is around 2226.26 Tunisian National Dinar (TND) per ha farm ranging from a minimum of 1016 to a high of 4370 TND/ha. The standard deviation of the water input vector indicates a large variability of the irrigation volume among the farms.

Table 1. Summary statistics of the sample variables

Variable		Mean	Standard Deviation	Min	Max
Output	Production value (TND/ha)	2226.26	636.46	1016	4370
Inputs	Water (m3/ha)	2696.24	1110.80	500	4500
	Labor expenses (TND/ha)	66.46	22.30	31.50	178.75
	Fertilizer expenses (TND/ha)	142.23	60.02	33	338

1TND≈0.70\$

The empirical Tobit regression model takes the following form:

$$IWE^* = \alpha_0 + \alpha_1 AGE + \alpha_2 EL + \alpha_3 EXP + \alpha_4 SIZE + \alpha_5 IS + \alpha_6 GDA + \alpha_7 IRR + \alpha_8 VAR + \alpha_9 PES + \varepsilon_i$$

where:

IWUE (Dependent variable): Irrigation water use efficiency scores

The independent variables are :

AGE = age (in years);

EL(Education level)= 1 if farmer has more or equal than secondary level, 0 otherwise

EXP = farming experience (in years);

SIZE = Farm size (in ha);

WS (water source)= 1 if the farmer uses 2 sources, 0 if one source

GDA (membership in a water users association) = 1 if farmer is member of a water user association, 0 if not

IRR (Irrigation management) = 1 if farmer respect the critical period of irrigation, 0 if not

VAR (wheat variety cultivated) = 1 if farmer use Maali variety, 0 if not (Maali variety is known to be among the most productive varieties in Tunisia and is highly promoted by policy makers)

PES (pesticide) =1 if farmer use pesticide during the crop cycle, 0 if not

4. Empirical results

4.1. Efficiency scores

SDEA model is estimated using the program GAMS (General Algebraic Modelling System). Table 2 presents the frequency distributions of overall technical efficiency and irrigation water use efficiency scores of the 170 farms considered in our study.

The mean farms technical efficiencies estimated under CRS and VRS assumptions are respectively 0.70 and 0.62. This implies that the current level of output can be produced using 30% less inputs on average. The difference between the VRS and CRS measures indicate that many farmers are not operating at an efficient scale (SE). The $SE_k = \frac{\theta_k^{CRS}}{\theta_k^{VRS}}$ is equal to 0.89.

The SDEA results however reveal a wide variation in individual efficiency scores across farms. These scores are ranging from 35.6% % to 100% under VRS and from 27% to 100% under CRS.

The average IWUE of our farm sample is about 0.44 under VRS and 0.41 under CRS. Farmers are then less efficient in the use of water compared to the use of other inputs indicating that an increase in the efficiency of water use will results in a better overall efficiency. A large range of water efficiencies are observed across 170 farms. As showed in the table 2 below, there are 129 farms with IWUE scores below 50%, 25 farms between 50-75%, and 16 farms with scores more than 75% under VRS. This result suggests that wheat farms may reduce their water use level while maintaining the same level of production.

Table 2: Frequency distribution of efficiency ratings of wheat farms in Chbika

E. Scores	Technical efficiency				IWUE			
	CRS		VRS		CRS		VRS	
	Number of farms	% of farms	Number of farms	% of farms	Number of farms	% of farms	Number of farms	% of farms
<0.25					35	0.21	38	0.22
0.25-0.50	38	22.40	11	6.50	81	0.48	91	0.54
0.5-0.75	105	61.80	109	64.10	35	0.21	25	0.15
>0.75	27	15.90	50	29.40	19	0.11	16	0.09
Average	0.62		0.70		0.41		0.44	
Min	0.27		0.36		0.12		0.11	
Max	1		1		1		1	

4.2. Factors explaining efficiencies of water use

Tobit regression explaining efficiency, as defined in equation 10 is estimated using Eview (econometric views) package. The results of the Tobit model estimation by Likelihood is listed in Table 3.

Tableau 3. Tobit estimation results of factors affecting IWUE

Variables	VRS		CRS	
	Coefficient	Z-Statistic	Coefficient	Z-Statistic
AGE	-0,001	-0,947	-0,002	-1,555
EL	-0,027	-0,698	-0,033	-0,920
EXP	0,004	2,742*	0,003	2,438*
SIZE	0,002	1,214	0,001	1,213
WS	0,357	4,175*	0,356	4,646*
GDA	0,103	2,755*	0,094	2,747*
IRR	0,162	4,094*	0,162	4,430*
VAR	0,169	4,337*	0,152	4,204*
PES	-0,012	-0,326	-0,013	-0,365
C	0,221	2,937*	0,263	3,769*
LR ¹	66,80*		70.22*	

* Signifiant at the 5% level.

Regarding to the Tobit model results, the likelihood test rejects a null hypothesis that all slope parameters are simultaneously null. This confirms that Tobit model is statistically significant. The majority of the estimated coefficients are significant at 5%. Furthermore, the estimated tobit model indicate the positive effect on water use efficiency of variety choice, irrigation sources, membership in water users association, irrigation management and experience. Finally, based on the empirical results, some suggestions are drawn in order to increase water use efficiency.

5. Conclusions

This study aims to measure the irrigation water use efficiency of a sample of wheat farms, located in central semi-arid Tunisia, and to identify its determinants. The Stochastic Data Envelopment Analysis SDEA was estimated based on data collected from 170 randomly selected farms for the 2010-2011 production season. The survey was conducted in Chbika region situated in the governorate of Kairouan.

The average technical efficiencies estimated under the CRS and VRS hypothesis of the farms in the sample are 0.70 and 0.62. This implies that the current level of output can be produced using 30% less inputs, on average. The average IWUE is about 0.44 under VRS and 0.41 under

¹ $LR = -2(\log L_r - \log L_u)$ where $\log L_u$ is the log-likelihood for the unrestricted model and $\log L_r$ is the log-likelihood for the model with p parameters restrictions imposed. The likelihood ratio statistic follows a chi-square distribution with p degrees of freedom.

CRS. In light of these research results, it seems that substantial decreases in water use could be attained by using the existing irrigation technology on wheat farms. This result is consistent with previous studies in Tunisia (Dhehibi et al. 2007; Albouchi et al., 2007, Frija et al. 2009; Chemak et al., 2010; Naceur et al., 2010; Chebil et al., 2012). Empirical studies listed above, have also used deterministic approach to measure water use efficiency. However, in the present study, SDEA was used in order to assess these IWUE scores.

Finally IWUE was found by many studies in Tunisia to be very low compared to the important efforts made by the government in order to save water. Even though, we tried to use a more comprehensive methodology in this paper, which is unique application in the Tunisian context, results about IWUE scores were still found to be very low. Thus, different methodologies are confirming the same results about inefficiency of irrigation water use.

Acknowledgments

This work was supported by the project « Enhancing Food Security in Arab Countries » Funded by ICARDA.

References

- Al Atiri, R. 2009. Politique du pays en matière de gestion de l'eau. Journée nationale de l'économie d'eau, INAT, 22 Mars, Tunis.
- Al Atiri, R., 2007. Evolution institutionnelle et réglementaire de la gestion de l'eau en Tunisie, Vers une participation accrue des usagers de l'eau ('Water Management and Institutional and Regulatory Trends in Tunisia. Towards Increased Water User Participation; in Sami Bouarfa, Marcel Kuper, Abdelhafid Debbarh (Scientific Publishers). The Future of Irrigated Agriculture in the Mediterranean. New Institutional Arrangements for Water Demand Management Wademed Seminar Proceedings, Cahors, France, 6 and 7 November 2006. Cirad, Montpellier, France.
- Albouchi, L., Bachta, M.S., Jacquet, F., 2007. Compared production efficiency in irrigated areas within a watershed. *New Medit*, Vol. VI - n. 3/2007.
- Chebil A., Frija A., Abdelkafi B., 2012. Irrigation water use efficiency in collective irrigated schemes of Tunisia: determinants and potential irrigation cost reduction. *Agricultural Economic Review*, Vol. 13, n°1, pp.39-48.
- Chemak, F., Boussemart J.P. and Jacquet F. 2010. Farming system performance and water use efficiency in the Tunisian semi-arid: data envelopment analysis. *International Transactions in operational research*, 17, 381-396.
- Coelli, T. 1995. Coelli. T. 1995. Recent Developments in Frontier Modelling and Efficiency Measurement. *Australian Journal of Agricultural Economics* 39(3):219-45.

- Dhehibi, B., Lachaal, L., Elloumi, M., Messaoud, A., 2007. Measuring irrigation water use efficiency using stochastic production frontier: An application on citrus producing farms in Tunisia. *AfJARE*. 1, no. 2, 99-114.
- Färe, R., Grosskopf, S., Lovell, C.A.K., 1994. *Production Frontiers*. Cambridge University Press, Cambridge.
- Frija A, Chebil A, Speelman S, Buysse J, Van Huylenbroeck G. 2009. Water use and technical efficiencies in horticultural greenhouses in Tunisia, (in English). “*Agricultural Water Management*”, Vol 96(11), 1509-1516, doi:10.1016/j.agwat.2009.05.006 .
- Land, K. C., A. A. K. Lovell, and S. Thore. 1993. Chance-Constrained Data Envelopment Analysis. *Managerial and Decision Economics* 14, 541–554.
- Lilienfeld, A. and Asmild, M. 2007. Estimation of excess water use in irrigated agriculture: a data envelopment analysis approach. *Agricultural Water Management*, 94: 73-82.
- Maddala, GS, 1983. *Limited dependent and qualitative variables in econometrics*. Cambridge University Press, Cambridge.
- Ministère de l’Agriculture (MA), 2010. *Annuaire des statistiques agricoles*, Tunisie.
- Ministère de l’Agriculture (MA), 2011. *Enquête sur les périmètres irrigués*, Tunisie.
- Naceur M., Sghaier M. et Bachta M.S., 2010. Water Use and Technical Efficiencies in Private Irrigated Perimeters in Zeuss-Koutine Watershed, South-Eastern Tunisia, BALWOIS 2010 - Ohrid, Republic of Macedonia - 25, 29 May 2010.
- Olesen, O.B. and Petersen, N.C., 1995. Chance constrained efficiency evaluation. *Management Science* 41, 442–457.
- Oude Lansink, A., Pietola, K., Bäckman, S., 2002. Efficiency and productivity of conventional and organic farms in Finland 1994-1997. *Eur Rev Agric Econ*. 29, 1, 51-65.
- Oude Lansink, A., Silva, E., 2004. Non-parametric production analysis of pesticides use in the Netherlands. *Journal of productivity analysis*. 21, 49-65.
- Seiford, L.M. 1996. Data Envelopment Analysis: The evolution of the state of the art (1978-1995). *Journal of Productivity Analysis*, 7, 99–138.
- Speelman S, D’Haese M, Buysse J, D’Haese L., 2008. A measure for the efficiency of water use and its determinants, a case study of small-scale irrigation schemes in North-West Province, South Africa. *Agricultural Systems*: 98:31-39.