



The World's Largest Open Access Agricultural & Applied Economics Digital Library

This document is discoverable and free to researchers across the globe due to the work of AgEcon Search.

Help ensure our sustainability.

Give to AgEcon Search

AgEcon Search

<http://ageconsearch.umn.edu>

aesearch@umn.edu

*Papers downloaded from **AgEcon Search** may be used for non-commercial purposes and personal study only. No other use, including posting to another Internet site, is permitted without permission from the copyright owner (not AgEcon Search), or as allowed under the provisions of Fair Use, U.S. Copyright Act, Title 17 U.S.C.*

No endorsement of AgEcon Search or its fundraising activities by the author(s) of the following work or their employer(s) is intended or implied.



Nonparametric Modelling of Co2 Emission Quota

Alfons G.J.M. Oude Lansink¹

¹ Wageningen University, Business Economics

Contribution appeared in Arfini, F. (Ed.) (2005) “Modelling Agricultural Policies: State of the Art and New Challenges”, proceedings of the 89th EAAE Seminar, pp. 375 - 383

February 2-5, 2005

Parma, Italy



UNIVERSITA' DEGLI
STUDI DI PARMA

Copyright 2005 by Alfons G.J.M. Oude Lansink. All rights reserved. Readers may make verbatim copies of this document for non-commercial purposes by any means, provided that this copyright notice appears on all such copies.

Nonparametric Modelling of CO₂ Emission Quota

Alfons G.J.M. Oude Lansink

Wageningen University, Business Economics*

Abstract

Dutch glasshouse firms are facing the introduction of a system of tradable CO₂ emission quota. Also, the firms will be faced with a cut of CO₂ emissions of approximately 5% by the year 2010. This paper employs a nonparametric method for modeling tradable CO₂ emissions of Dutch glasshouse firms. The method is capable of generating shifts in CO₂ emissions across the sample of firms. Also, changes in volumes of outputs produced and inputs used are computed. Results show that firms using a conventional heating technology will be net purchasers of CO₂ emissions, whereas firms using more advanced heating technologies will sell part of their emission quota.

Keywords: DEA, CO₂ emissions, tradable emissions, non-parametric modelling.

Introduction

The Dutch glasshouse industry is an important user of energy and accounts for approximately 4% of greenhouse gas emissions in the Netherlands. In 1995, the Dutch glasshouse industry made a covenant with the government aiming at reducing the use of energy. In the covenant, the Dutch glasshouse industry has to improve its energy efficiency by 65% in 2010 compared to the level of 1980 (Stuurgroep Landbouw en Milieu, 2000). The Dutch glasshouse industry may improve its energy efficiency by investing in new energy saving technologies or, alternatively by improving the efficiency of the current production potential. Information about the environmental performance of glasshouse firms can be used for assessing the potential for reducing the use of energy and emissions of carbon dioxide (CO₂) using different current available energy saving technologies. This information can be useful in guiding the process of energy efficiency improvement under the covenant and reduction of CO₂ emissions as required under the Kyoto protocol.

* Hollandseweg 1, 6706 KN Wageningen, Phone: +31-317-485194; E-mail: Alfons.oudelansink@wur.nl.

Currently, the glasshouse sector is facing the introduction of a system of tradeable CO₂ emissions and the maximum allowed CO₂ emission level for the glasshouse industry as a whole will be cut by approximately 5% (LTO, 2005). The extent to which quota are redistributed by allowing for trade critically depends on the variation in the firm-specific marginal value of CO₂ quota. Marginal values are likely to differ across firms, due for example to differences in technology and managerial performance. Technological differences and differences in managerial performance between firms are frequently measured by technical efficiency. Therefore, the size of marginal abatement costs may be closely related to technical efficiency (Oude Lansink, 2003) and profitability (Brannlund et al., 1998). However, the relationship between technical efficiency and marginal abatement costs is still a largely neglected area of research.

Tradeable emission rights have been frequently modelled in the literature using parametric approaches based on micro-econometric models (see e.g. Boots et al., 1997). Oude Lansink (2003) used a parametric approach for modelling CO₂ emissions. However, the parametric approach and consequently the computation of the marginal value of quota is restricted by the functional form employed.

The Data Envelopment Analysis (DEA) approach has been proposed as a nonparametric method for evaluating producers performance in the presence of adverse environmental impacts (e.g., Färe et al., 1989; Ball et al., 1994; Tyteca, 1997). Färe et al. (1989) modify the efficiency measures proposed by Färe, Grosskopf and Lovell (1985) to allow for an asymmetric treatment of desirable and undesirable outputs. Following Färe et al., (1989) and Pittman (1983), Ball et al. (1994) adjust a conventional measure of total factor productivity growth by incorporating undesirable outputs in the production process. The DEA approach is attractive for its flexibility and computational ease. Moreover, it avoids assumptions on the functional form of the investigated relationships. A disadvantage of the DEA method is that it likely confounds efficiency with errors in the data that result from e.g. stochastic events (weather) or measurement of variables. Levring Andersen and Bogetoft (2003) applied DEA to model tradable quota in fisheries.

The objective of this paper is threefold. First, following Levring Andersen and Bogetoft, it develops a nonparametric approach to modelling tradable CO₂ emissions in the Dutch glasshouse industry. The approach adopted in this research allows for computing the redistribution across firms of CO₂ emissions. Moreover, the approach allows for computing changes in volumes of variable inputs and outputs as a result of quota trade and the reduction of the total CO₂ quota level by 5%. Second, this paper analyses the relation between various efficiency measures and quota trade. Third, this paper investigates the relation between heating technologies and demand for additional CO₂ quota.

The remainder of this paper is structured as follows. The next section presents the DEA models that are used for modelling (tradeable) CO₂ emissions. This is followed by a discussion of data. Next the results are presented and the paper concludes with comments.

DEA models for CO₂ emissions

The discussion of the DEA models starts from a set of observations of firms in a sample that use a *vector* of desirable variable inputs (x^v), CO₂ emissions (w) and a *vector* of fixed inputs (x^f) to produce a desirable output (y).

Input-oriented overall technical efficiency for each firm i , $i=1, \dots, N$, is calculated from the following non-linear programming problem:

$$\begin{aligned}
 & \underset{\theta_w, \lambda}{\text{Min}} \theta_w \\
 \text{s.t.} \quad & -y_i + Y\lambda \geq 0 \\
 & \theta_w x_i^v - X^v \lambda \geq 0 \\
 & \theta_w w_i - W\lambda \geq 0 \\
 & \theta_w x_i^f - X^f \lambda \geq 0 \\
 & N1' \lambda = 1 \\
 & \lambda \geq 0
 \end{aligned} \tag{1}$$

where θ_w is the overall technical efficiency score ($\theta_w \in [0,1]$) for the i -th firm under the assumption of weak disposability of CO₂ emissions, Y is the $(1 \times N)$ vector of observed outputs, X^v is the matrix of observed desirable variable inputs, W is $(1 \times N)$ vector of CO₂ emissions, X^f is the matrix of observed fixed inputs and λ is a $N \times 1$ vector of intensity variables (firm weights). The value of the firm weights identifies the firms that determine the production frontier. The constraint $N1'\lambda=1$ (with $N1'$ being an $N \times 1$ vector of ones) implies the sum of the lambda's equals one and allows for a variable returns to scale (VRS) technology. Overall technical efficiency represents the maximum proportional reduction of all inputs subject to the constraints imposed by the observed outputs and the technology.

Using the notion of subvector efficiency proposed by Färe, Grosskopf and Lovell (1994), CO₂ technical efficiency is calculated for each firm i by solving the following problem:

$$\begin{aligned}
 & \underset{\gamma_w^C, \lambda}{\text{Min}} \gamma_w^C \\
 \text{s.t.} \quad & -y_i + Y\lambda \geq 0 \\
 & x_i^v - X^v \lambda \geq 0 \\
 & \gamma_w^C w_i \geq W\lambda \\
 & x_i^f - X^f \lambda \geq 0 \\
 & N1' \lambda = 1 \\
 & \lambda \geq 0
 \end{aligned} \tag{2}$$

where γ_w^C is the CO₂ technical efficiency score for firm i and all the other variables are defined as before. CO₂ technical efficiency represents the maximum contraction of this input, holding outputs and other inputs constant. Therefore, the CO₂ efficiency model involves finding a frontier that minimises the quantity of CO₂ emissions.

Profit efficiency is computed by solving the LP problem in (3).

$$\begin{aligned}
 & \underset{\lambda, x_i^{*v}, y_i^*, w_i^*}{Max} \quad p \cdot y_i^* - r \cdot x_i^{*v} \\
 & s.t. \quad -y_i + Y\lambda \geq 0 \\
 & \quad \quad x_i^{*v} - X^v \lambda \geq 0 \\
 & \quad \quad w_i^* - W\lambda \geq 0 \\
 & \quad \quad x_i^f - X^f \lambda \geq 0 \\
 & \quad \quad N1' \lambda = 1 \\
 & \quad \quad \lambda \geq 0
 \end{aligned} \tag{3}$$

where x_i^{*v} and y_i^* denote variable input and output quantities that maximise variable profit, defined as revenue minus costs of variable inputs. Profit efficiency is computed as the ratio of actual and maximum obtainable profit: π_i / π_i^* , where π_i is actual profit defined as

$p \cdot y_i - r \cdot x_i^v$ and π_i^* is actual profit defined as $p \cdot y_i^* - r \cdot x_i^{*v}$.

$$\begin{aligned}
 & \underset{\lambda, x_i^{*v}, y_i^*, w_i^*}{Max} \quad \sum_{i=1}^N p \cdot y_i^* - r \cdot x_i^{*v} \\
 & s.t. \quad -y_i^* + Y\lambda \geq 0 \quad \forall i \\
 & \quad \quad x_i^{*v} - X^v \lambda \geq 0 \quad \forall i \\
 & \quad \quad w_i^* - W\lambda \geq 0 \quad \forall i \\
 & \quad \quad N1' w_i^* \leq \bar{W} \quad \forall i \\
 & \quad \quad x_i^f - X^f \lambda \geq 0 \quad \forall i \\
 & \quad \quad N1' \lambda = 1 \quad \forall i \\
 & \quad \quad \lambda \geq 0 \quad \forall i
 \end{aligned} \tag{4}$$

The fourth constraint ensures that the sum the CO₂ emission quota across all firms in the sample does not exceed the maximum total emission level \bar{W} . The difference between the variable input and output volumes computed in (4) and (3) indicates the change in the input-output mix as a result of the introduction of system of tradable quota and \bar{W} .

Data

Data on specialised vegetables firms covering the year 1995 come from a stratified sample of Dutch glasshouse firms keeping accounts on behalf of the LEI accounting system. The firms typically remain in the panel for a maximum of eight years, so the panel is incomplete. Firms rotate in and out the sample to avoid a selection bias which arises when firms improve their performance by their presence in the accounting system. The data set used for estimation contains 73 firms.

One output and six inputs (energy, materials, services, structures, machinery and installations and labour) are distinguished. Output consists mainly of vegetables. Other outputs included are fruits, potplants and flowers. Energy consists of gas, oil and electricity, as well as heat deliveries by electricity plants. Materials consist of seeds and planting materials, pesticides, fertilisers and other materials. Services are those provided by contract workers and from storage and delivery of outputs.

Fixed inputs are structures (buildings, glasshouses, land and paving), machinery and installations and labour. Labour is measured in quality-corrected man years, and includes family as well as hired labour. Labour is assumed to be a fixed input because a large share of total labour consists of family labour. Flexibility of hired labour is further restricted by the presence of permanent contracts and by the fact that hiring additional labour involves search costs for the firm operator. The quality correction of labour is performed by the LEI and is necessary to aggregate labour from able-bodied adults with labour supplied by young people (e.g., young family members) or partly disabled workers. Capital in structures, machinery and installations is measured at constant 1985 prices and is valued in replacement costs¹.

Data on CO₂ emissions have been obtained from the LEI and are measured as tons of CO₂ emission per year. CO₂ emissions are calculated from physical quantities of fossil fuels (mainly methane gas) that are used for heating and CO₂ fertilisation in the glasshouse (see Cordenier (1999) for more details). Therefore, CO₂ emissions and energy are independent factors, since energy consists of components that do not cause CO₂ emissions on the firms, i.e. heat delivery and electricity. The CO₂ emissions are partly incorporated in plants because CO₂ serves as a fertiliser. Therefore, the data overestimate the true CO₂ emissions, although the degree of overestimation is small (Cordenier, 1999).

Tornqvist price indexes are calculated for output and the three composite variable inputs with prices obtained from the LEI-DLO/CBS. The price indexes vary over the years but not over the firms, implying differences in the composition of inputs and output or quality differences are reflected in the quantity (Cox and Wohlgenant, 1986). Implicit quantity indexes are generated as the ratio of value to the price index.

¹ The deflators for capital in structures and machinery and installations are calculated from the data supplied by the LEI accounting system. Comparison of the balance value in year *t* and the balance value in year *t*-1 gives the yearly price correction used by the LEI. This price correction is used to construct a price index for capital and a price index for machinery and installations. These price indices are used as deflators.

The firms in the sample use different heating technologies. Most firms (55%) use traditional heating based on the use of a central heating boiler; 31% of the firms use traditional heating in combination with heat storage and 10% and 4% of the firms in the sample use co-generators² and heat deliveries by electricity generating plants, respectively. A more detailed description of the data can be found in Table 1.

Table 1. Variables and Descriptive Statistics.

Variable	Dimension	Mean	Standard Deviation
Output	100.000 Guilders	12.48	7.76
Energy	100.000 Guilders	2.00	1.31
Materials	100.000 Guilders	1.67	1.13
Services	100.000 Guilders	1.06	0.59
Structures	100.000 Guilders	10.99	7.75
Machinery and Installations	100.000 Guilders	3.65	2.89
Labor	Man years	7.60	4.19
CO ₂ Emission	1.000 Ton	15.00	10.0

Results

Solutions have been obtained for all models (1)-(4) and for all firms in the sample using the program GAMS. The LP model in (4) assumes that the firms in the sector are faced with a 5% overall cut in CO₂ quota.

Results in Table 2 show that buyers of CO₂ quota have a higher technical and CO₂ efficiency than sellers of CO₂ quota. The profit efficiency of buyers and sellers is approximately the same. Buyers purchase, on average 11.953 thousand tons of CO₂, whereas the average volume sold by sellers equals 9.459 thousand tons.

Table 2. Efficiency and traded CO₂ emissions for buyers and sellers of CO₂ emission quota.

	Technical Efficiency	CO ₂ efficiency	Profit Efficiency	Net purchase CO ₂
Buyers	0.913	0.727	0.788	11.953
Sellers	0.894	0.646	0.803	-9.459

Table 3 shows that buyers of quota increase their volume of output by 10%, which is at the cost of a substantial (44.8%) increase in the use of energy. Increases in the volumes of materi-

² Co-generators are installations that combine the generation of electricity and heat.

als and services are smaller. Sellers of CO₂ quota reduce the volume of output by 7.8 % and reduce their demand for energy by 32.3%.

Table 3. Change in outputs and variable inputs for buyers and sellers of CO₂ emission quota.

	Output	Energy	Materials	Services
Buyers	0.101	0.448	0.014	0.203
Sellers	-0.078	-0.323	-0.002	-0.180

Results in Table 4 provide insight in the impact of heating technologies on behaviour in the market for CO₂ emissions. Firms using heating boilers, on average, purchase 1.175 thousand tons of CO₂. Firms using more energy saving technologies, on average sell CO₂ quota. Firms using a heating boiler have a CO₂ efficiency that is lower than the CO₂ efficiency of firms using more advanced technologies. The overall technical efficiency of firms using a central heating boiler is high.

Table 4. Efficiency and traded CO₂ emissions for firms with different heating technologies.

	Technical Efficiency	CO ₂ efficiency	Profit Efficiency	Net purchase CO ₂
Heating boiler	0.986	0.657	0.743	1.175
Boiler + storage	0.920	0.777	0.847	-0.974
Co-generator	0.905	0.683	0.843	-2.640
Heat delivery	0.998	0.995	0.945	-0.526

Results in Table 5 show the impact of tradeable CO₂ quota and the reduction of the CO₂ quota for the whole sector by 5% on volumes of outputs and variable inputs of firms with different heating technologies. Firms using heating boilers, on average increase their output volume by 9.4% and increase their use of energy by 42.1%. The impact for firms using more advanced heating technologies is much smaller, particularly for firms using heat delivery. Firms using co-generators sell a relatively large quantity of CO₂ quota; the impact on volumes of output and demand for energy is, nevertheless small.

Table 5. Change in outputs and variable inputs for firms with different heating technologies.

	Output	Energy	Materials	Services
Heating boiler	0.094	0.421	0.026	0.194
Boiler + storage	0.003	0.034	-0.043	0.035
Co-generator	-0.011	-0.049	0.040	-0.118
Heat delivery	0.000	-0.022	-0.003	-0.057

Conclusions

This paper employs a nonparametric method for modelling tradable CO₂ emissions of Dutch glasshouse firms. The method is capable of generating shifts in CO₂ emissions across the sample of firms. Also, changes in volumes of outputs produced and inputs used are computed. The method is applied to a sample of vegetables firms in the Netherlands.

Results show that firms using a conventional heating technology will be net purchasers of CO₂ emissions, whereas firms using more advanced heating technologies will sell part of their emission quota. Net purchasers of CO₂ emission have a higher technical and CO₂ efficiency than sellers of quota. However, the profit efficiency of buyers and sellers is approximately equal.

The method developed in this paper provides a flexible tool for analysing the relation between various efficiency measures and behavior in the market for CO₂ emissions. The application is restricted to a sample of vegetables producers. In the system that will be designed for the glasshouse industry, these firms are also able to trade with firms specialised in potted plants and cut flowers. Future research should consider trade with other sectors of the economy. This is because these options affect the price of CO₂ quota and may result in an overall expansion or contraction of the sector.

References

- Agricultural Economics Research Institute and Netherlands Central Bureau of Statistics (LEI/CBS, 1988, 1990, 1994, 1997): *Landbouwcijfers*, The Hague.
- Ball V.E., Lovell C.A.K., Nehring R.F. and Somwaru A. (1994): "Incorporating Undesirable Outputs into Models of Production", *Cahiers D'Économie et Sociologie Rurales*, 31: 60-73.
- Brännlund R., Chung Y., Färe R. and Grosskopf S. (1998): "Emissions trading and profitability: The Swedish pulp and paper industry", *Environmental and Resource Economics*, 12: 345-356.
- Boots M., Oude Lansink A. and Peerlings J. (1997): "Transaction costs and distortions in Dutch Milk quota trade", *European Review of Agricultural Economics*, 24: 31-46.
- Cordenier M.F.C. (1999): *Emissiereductie in de glastuinbouw: Een literatuurstudie en een effect rapportage*, Msc thesis, Wageningen University.
- Cox T.L., Wohlgenant M.K. (1986): "Prices and Quality Effects in Cross-Sectional Demand Analysis", *American Journal of Agricultural Economics*, 68: 908-919.
- Färe R., Grosskopf S., Lovell C.A.K. (1994): *Production frontiers*, Cambridge, Cambridge University Press.
- Färe R., Grosskopf S., Lovell C.A.K. and Pasurka C. (1989): "Multilateral Productivity Comparisons when some Outputs are Undesirable: A Nonparametric Approach", *Review of Economics and Statistics*, 71: 90-98.

- Färe R., Grosskopf S. and Lovell C.A.K. (1985): *The Measurement of Efficiency of Production*, Dordrecht, Kluwer-Nijhoff Publishing.
- Levring Andersen J. and Bogetoft P. (2003): "Quota trading and profitability: Theoretical models and applications to Danish fisheries", KVL, working paper.
- Oude Lansink A. (2000): "Productivity growth and efficiency measurement: a dual approach", *European Review of Agricultural Economics*, 27: 59-73.
- Oude Lansink A. and Silva E. (2003): "CO₂ and Energy Efficiency of Different Heating Technologies in the Dutch Glasshouse Industry", *Environmental and Resource Economics* 24: 395-407.
- Oude Lansink A. (2003): "Technical efficiency and CO₂ abatement policies in the Dutch glasshouse industry", *Agricultural Economics*, 28: 99-108.
- Pittman R.W. (1983): "Multilateral Productivity Comparisons with Undesirable Outputs", *Economic Journal*, 93: 883-91.
- Stuurgroep Landbouw en Milieu (2000): *Energieflits* 4, March 2000.
- Tyteca D. (1997): "Linear Programming Models for the Measurement of Environmental Performance of Firms: Concepts and Empirical results", *Journal of Productivity Analysis*, 8: 183-197.
- United Nations (1997): *Kyoto protocol to the United Nations framework convention on climate change*, Kyoto, Japan.